

DOCK RITE, INC.

18250 203rd Street ~ Hutchinson, MN. 55350 ~ USA
Phone 320-587-0644 ~ Fax 320-587-3109
1-888-407-3292

ADJUSTABLE LEVELING LEG KIT INSTRUCTIONS FOR VERTICAL LIFT

1. If already drilled for adjustable legs and has adjustment sticker on each corner go to step 5. If lift not drilled for adjustable legs measure from top of lift corner down 17.5" and place a mark with a pencil.
2. Then place top of adjustment sticker below pencil mark with holes parallel to the on-off direction of the lift (SEE PICTURE).
3. Next using a 1/2" drill bit, drill top hole of sticker through both sides of tube (be careful to keep drill level and square to the tube).
4. Now using a 7/8" drill bit, drill bottom hole of sticker through front side of tube only.
5. Lift boatlift side up (or to the side if apart) and insert adjustable leg making sure Allen head adjuster is facing 7/8" hole in tube. Also make sure bottom pad hole is facing across lift. Insert pin through top hole in sticker and top hole in adjustable leg, secure with clip.
6. Fasten pad to bottom of adjustable leg.
7. Repeat above step on remaining lift corners.
8. Using either bit supplied for drill or handle adjust legs so lift is sitting level in the water, and at proper height to load and unload your boat. **(CAUTION: DO NOT ADJUST LEGS WITH BOAT OR PONTOON ON THE LIFT)**

PARTS LIST:

4- ADJUSTABLE LEGS
4- 1/2"X3" PINS
4- 1/8" CLIPS
4- ADJUSTMENT STICKERS
1- DRILL HEX BIT
1- HEX BIT HANDLE

